

ELECTROFUSION  
SADDLES

MOLDED  
FOR YOUR  
INDUSTRY

IntegriFuse™



 **INTEGRITY**  
Fusion Products, Inc.

TOLL FREE 1-888-770-6330

INTEGRITYFUSION.COM

# The difference MOLDED Makes

Integrity Fusion continues to be the market leader in electrofusion fittings, by offering innovative solutions to all of your fusible needs. Our IntegriFuse brand EF Saddles are molded in sizes up through 48" IPS base and fully pressure rated to SDR 11. Many of our EF Saddles are offered with Flexible Bases to fit several sizes of pipe mains, allowing for fewer stock items to fit a large range of projects. In addition, the flexible base allows for better fit on the pipe, helping to eliminate any gaps between the fitting and the pipe. All IntegriFuse EF Saddles come standard with the appropriate strap(s) for installation, eliminating the need for additional clamps or tooling.

IntegriFuse EF Fittings are manufactured from the highest quality black high density bimodal polyethylene copolymer resin designed for use in, but not limited to, potable water, natural gas, industrial, landfill, oil & gas, and mining applications.

All IntegriFuse fittings meet ASTM –D2513 & ASTM D3261 (where applicable)

Integrity Fusion Products, Inc.  
270 Parkade Court  
Peachtree City, GA 30269

P: 1-888-770-6330 • P: 770-632-7530

F: 770-632-7540

E: [Info@IntegrityFusion.com](mailto:Info@IntegrityFusion.com)



**Electrofusion Branch Saddle** - Water - 200 PSI (ASTM) / 232 PSI (ISO) | Gas - 100 PSI @ 73° F Sustainable  
Maximum Operating Pressure | Suitable for use on IPS/DIPS SDR 11 to SDR 17 HDPE Pipe

Outlet (DE1)	Base (DE)	Height (H)	Number of Straps Incl.	Item Code	Notes
2" IPS	2" IPS	3.50"	1	200285	
2" IPS	3" IPS	3.50"	1	200279	
2" IPS	4" IPS	3.50"	1	200276	
2" IPS	4" DIPS	3.50"	1	200275	
2" IPS	6" IPS - 6" DIPS	3.50"	1	200274	FM 220
2" IPS	8" IPS/DIPS - 10" DIPS	3.50"	1	200200	FM 220
2" IPS	12" IPS/DIPS - 18" IPS	3.50"	1	200203	FM 220
2" IPS	20" IPS/DIPS - 22" IPS	3.50"	2	200241	FM 220
2" IPS	20" IPS/DIPS - 36" IPS	3.50"	2	200254	FM 220
3" IPS	6" IPS - 6" DIPS	3.50"	1	200281	FM 220
3" IPS	8" IPS /DIPS- 10" DIPS	3.50"	1	200217	FM 220
3" IPS	12" IPS/DIPS - 18" IPS	3.50"	1	200223	FM 220
3" IPS	20" IPS/DIPS - 22" IPS	3.50"	2	200210	FM 220
3" IPS	20" IPS/DIPS - 36" IPS	3.50"	2	200255	FM 220
4" IPS	6" IPS	4.30"	2	200277	FM 220
4" IPS	8" IPS	4.30"	2	200218	FM 220
4" IPS	10" IPS	4.30"	2	200220	FM 220
4" IPS	12" IPS/DIPS - 16" DIPS	4.30"	2	200206	FM 220
4" IPS	18" IPS /DIPS- 20" DIPS	4.30"	2	200234	FM 220
4" IPS	22" IPS/DIPS - 26" IPS	4.30"	2	200212	FM 220
4" IPS	28" IPS/DIPS - 32" IPS	4.30"	2	200272	FM 220
4" IPS	34" IPS - 42" IPS	4.30"	2	200216	FM 220

Other sizes and SDR options are available for special order \* Flex Base Saddles cover all sizes in range listed as "BASE".

NSF/ANSI/CAN-61 and NSF/ANSI-372

Manufactured in accordance to ASTM F1055

Manufactured with resin having a material designation code of PE3408 / PE4710 / PE100 resin to comply to ASTM D3350.



# The difference MOLDED Makes

Integrity Fusion continues to be the market leader in electrofusion fittings, by offering innovative solutions to all of your fusible needs. Our IntegriFuse brand EF Saddles are molded in sizes up through 48" IPS base and fully pressure rated to SDR 11. Many of our EF Saddles are offered with Flexible Bases to fit several sizes of pipe mains, allowing for fewer stock items to fit a large range of projects. In addition, the flexible base allows for better fit on the pipe, helping to eliminate any gaps between the fitting and the pipe. All IntegriFuse EF Saddles come standard with the appropriate strap(s) for installation, eliminating the need for additional clamps or tooling. difficult to utilize butt fusion equipment.

IntegriFuse EF Fittings are manufactured from the highest quality black high density bimodal polyethylene copolymer resin designed for use in, but not limited to, potable water, natural gas, industrial, landfill, oil & gas, and mining applications.

All IntegriFuse fittings meet ASTM –D2513 & ASM D3261(where applicable)

Integrity Fusion Products, Inc.

270 Parkade Court

Peachtree City, GA 30269

P: 1-888-770-6330 • P: 770-632-7530

F: 770-632-7540

E: Info@IntegrityFusion.com



**Electrofusion Branch Saddle** - Water - 200 PSI (ASTM) / 232 PSI (ISO) | Gas - 100 PSI @ 73° F Sustainable  
Maximum Operating Pressure | Suitable for use on IPS/ DIPS SDR 11 to SDR 17 HDPE Pipe

Outlet (DE1)	Base (DE)	Height (H)	Number of Straps Incl.	Item Code	Notes
6" IPS	10" IPS	4.30"	2	200278	FM 220
6" IPS	12" IPS	4.30"	2	200224	FM 220
6" IPS	18" IPS/DIPS - 20" DIPS	4.30"	2	200235	FM 220
6" IPS	22" IPS/DIPS - 26" IPS	4.30"	2	200214	FM 220
6" IPS	28" IPS/DIPS - 32" IPS	4.30"	2	200273	FM 220
6" DIPS	12" DIPS	4.30"	2	200231	
8" IPS	12" IPS	7.90"	2	200225	
8" IPS	16" IPS	7.90"	2	TBD	
8" IPS	18" IPS	7.90"	2	TBD	
8" IPS	22" IPS	7.90"	2	200211	
8" IPS	24" IPS	7.90"	2	TBD	
8" IPS	26" IPS	7.90"	2	200213	
8" IPS	30" IPS	7.90"	2	TBD	
8" IPS	36" IPS	7.90"	2	TBD	
10" IPS	16" IPS	7.90"	2	TBD	
10" IPS	18" IPS	7.90"	2	TBD	
10" IPS	20" IPS	7.90"	2	TBD	
10" IPS	24" IPS	7.90"	2	TBD	
12" IPS	32" IPS	7.90"	2	200215	

Other sizes and SDR options are available for special order

\* Flex Base Saddles cover all sizes in range listed as "BASE".

NSF/ANSI/CAN-61 and NSF/ANSI-372 - Manufactured in accordance to ASTM F1055  
Manufactured with resin having a material designation code of PE3408 / PE4710 / PE100  
resin to comply to ASTM D3350.

