




Product Family:	Injection Molded Butt Fusion Fitting	Fitting Design:	45° Wye
Resin Status:	NSF Listed Bi-Modal Virgin Resin	Nominal Pipe Sizes:	2" – 8"
Resin Type:	ASTM D3350 designated PE3408/PE4710/PE100	Nominal Pipe Standard:	IPS
Resin Cell Class:	4455574-CC3	Currently Available SDR's:	17, 11
Manufactured and tested to meet requirements of: ASTM D2513, ASTM D3261, ANSI/AWWA C901 & C906, FM 1613, NSF 61 For use on pipe and fittings conforming to: ASTM D2513, ASTM D3035, ASTM F-714			

For Material and Testing information, please refer to our Molded Fitting Specification Sheet.

IPS

SDR 17 (standard dimension ratio)

125 PSI (MAOP @ 73.4° F)

Nominal Size	A [in.]	B [in.]	C [in.]	D [in.]	E [in.]	Weight [lbs.]	Item Code	FM Class
2" IPS	23.74	5.28	13.10	2.375	0.140	2.10	100901	-----
3" IPS	24.56	5.90	13.10	3.500	0.206	3.00	100903	-----
4" IPS	28.50	5.70	20.60	4.500	0.264	7.00	100905	-----
6" IPS	34.65	5.30	26.00	6.625	0.390	19.8	100907	-----
8" IPS	37.40	5.70	27.56	8.625	0.507	44.9	100909	-----

IPS

SDR 11 (standard dimension ratio)

200 PSI (MAOP @ 73.4° F)

Nominal Size	A [in.]	B [in.]	C [in.]	D [in.]	E [in.]	Weight [lbs.]	Item Code	FM Class
2" IPS	23.74	5.28	13.10	2.375	0.216	2.20	100900	-----
3" IPS	24.56	5.90	13.10	3.500	0.318	4.70	100902	-----
4" IPS	28.50	5.70	20.60	4.500	0.409	9.70	100904	-----
6" IPS	34.65	5.30	26.00	6.625	0.603	26.2	100906	-----
8" IPS	37.40	5.70	27.56	8.625	0.785	52.0	100908	-----